



WAGATE® AVSTÄNGNINGSVENTILER

TECHNICAL SPECIFICATION

Model no.	RVM-TG1000
Nominal Diameter	DN/OD 1000
Available valve body mtrl.	PE
Fasteners mtrl.	AISI 316, Marine grade Stainless Steel
Weight	570 kg
Max On-seating Pressure	5 mH ₂ O
Max Off-seating pressure	5 mH ₂ O
Torque nm	47.00 nm
Thread pitch	5 mm
Dimension	1000 mm
Øs	30 mm
Torque nm	47 nm
Thread pitch	5 mm
Max On-seating Pressure	5 mH ₂ O
Max Off-seating pressure	5 mH ₂ O
L1	700 mm
Thickness valve body	230 mm
Inner Diameter	923.60 mm
Outer Diameter	1000 mm
W	1112 mm
H1	1948 mm
L	1510 mm
Sealed for one-sided pressure	1
Sealed for two-sided pressure	1

- Tests performed at room temperature (16-20°C).
- Reference point measured from bottom of pipe."

© 2022 Wapro AB. This document is subject to copyrights owned by Wapro AB. Any amendments, republication, retransmission, and/or reproduction of all or any part of the document is expressly prohibited, unless the copyright owner of the material has expressly granted its prior written consent. All other rights are reserved.

Wapro AB
Munkahusvägen 103
SE-37431 Karlshamn

+46 (0)454 185 10
wapro@wapro.com

Reg.nr: 556352-1466
Registered office:
Karlshamn, Sweden
VAT nr: SE556352146604

**HOLDING BACK
THE FLOOD**