



# WAGATE® AVSTÄNGNINGSVENTILER

## TECHNICAL SPECIFICATION

Model no.	RVM-TG1200
Nominal Diameter	DN/OD 1200
Available valve body mtrl.	PE
Fasteners mtrl.	AISI 316, Marine grade Stainless Steel
Weight	689 kg
Max On-seating Pressure	5 mH <sub>2</sub> O
Max Off-seating pressure	5 mH <sub>2</sub> O
Torque nm	67.00 nm
Thread pitch	5 mm
Dimension	1200 mm
Øs	30 mm
Torque nm	67 nm
Thread pitch	5 mm
Max On-seating Pressure	5 mH <sub>2</sub> O
Max Off-seating pressure	5 mH <sub>2</sub> O
L1	800 mm
Thickness valve body	250 mm
Inner Diameter	1108.20 mm
Outer Diameter	1200 mm
W	1312 mm
H1	2549 mm
L	1708 mm
Sealed for one-sided pressure	1
Sealed for two-sided pressure	1

- Tests performed at room temperature (16-20°C).  
- Reference point measured from bottom of pipe."

© 2022 Wapro AB. This document is subject to copyrights owned by Wapro AB. Any amendments, republication, retransmission, and/or reproduction of all or any part of the document is expressly prohibited, unless the copyright owner of the material has expressly granted its prior written consent. All other rights are reserved.

**Wapro AB**  
Munkahusvägen 103  
SE-37431 Karlshamn

+46 (0)454 185 10  
wapro@wapro.com

Reg.nr: 556352-1466  
Registered office:  
Karlshamn, Sweden  
VAT nr: SE556352146604

**HOLDING BACK  
THE FLOOD**