



WAGATE® AVSTÄNGNINGSVENTILER

TECHNICAL SPECIFICATION

Model no.	RVM-TG160
Nominal Diameter	DN/OD 160
Available valve body mtrl.	PE
Fasteners mtrl.	AISI 316, Marine grade Stainless Steel
Weight	14 kg
Max On-seating Pressure	40 mH ₂ O
Max Off-seating pressure	40 mH ₂ O
Torque nm	11.00 nm
Thread pitch	4 mm
Dimension	160 mm
Øs	16 mm
Torque nm	11 nm
Thread pitch	4 mm
Max On-seating Pressure	40 mH ₂ O
Max Off-seating pressure	40 mH ₂ O
L1	150 mm
Thickness valve body	162 mm
Inner Diameter	141 mm
Outer Diameter	160 mm
W	250 mm
H1	480 mm
L	396 mm
Sealed for one-sided pressure	1
Sealed for two-sided pressure	1

- Tests performed at room temperature (16-20°C).
- Reference point measured from bottom of pipe."

© 2022 Wapro AB. This document is subject to copyrights owned by Wapro AB. Any amendments, republication, retransmission, and/or reproduction of all or any part of the document is expressly prohibited, unless the copyright owner of the material has expressly granted its prior written consent. All other rights are reserved.

Wapro AB
Munkahusvägen 103
SE-37431 Karlshamn

+46 (0)454 185 10
wapro@wapro.com

Reg.nr: 556352-1466
Registered office:
Karlshamn, Sweden
VAT nr: SE556352146604

**HOLDING BACK
THE FLOOD**