



# WAGATE® AVSTÄNGNINGSVENTILER

## TECHNICAL SPECIFICATION

Model no.	RVM-TG315
Nominal Diameter	DN/OD 315
Available valve body mtrl.	PE
Fasteners mtrl.	AISI 316, Marine grade Stainless Steel
Weight	37 kg
Max On-seating Pressure	40 mH <sub>2</sub> O
Max Off-seating pressure	40 mH <sub>2</sub> O
Torque nm	31.00 nm
Thread pitch	4 mm
Dimension	315 mm
Øs	16 mm
Torque nm	31 nm
Thread pitch	4 mm
Max On-seating Pressure	40 mH <sub>2</sub> O
Max Off-seating pressure	40 mH <sub>2</sub> O
L1	250 mm
Thickness valve body	162 mm
Inner Diameter	277.60 mm
Outer Diameter	315 mm
W	386 mm
H1	735 mm
L	596 mm
Sealed for one-sided pressure	1
Sealed for two-sided pressure	1

- Tests performed at room temperature (16-20°C).  
- Reference point measured from bottom of pipe."

© 2022 Wapro AB. This document is subject to copyrights owned by Wapro AB. Any amendments, republication, retransmission, and/or reproduction of all or any part of the document is expressly prohibited, unless the copyright owner of the material has expressly granted its prior written consent. All other rights are reserved.

**Wapro AB**  
Munkahusvägen 103  
SE-37431 Karlshamn

+46 (0)454 185 10  
wapro@wapro.com

Reg.nr: 556352-1466  
Registered office:  
Karlshamn, Sweden  
VAT nr: SE556352146604

**HOLDING BACK  
THE FLOOD**