



# WAGATE® AVSTÄNGNINGSVENTILER

## TECHNICAL SPECIFICATION

Model no.	RVM-TG500
Nominal Diameter	DN/OD 500
Available valve body mtrl.	PE
Fasteners mtrl.	AISI 316, Marine grade Stainless Steel
Weight	89 kg
Max On-seating Pressure	20 mH <sub>2</sub> O
Max Off-seating pressure	20 mH <sub>2</sub> O
Torque nm	45.00 nm
Thread pitch	4 mm
Dimension	500 mm
Øs	18 mm
Torque nm	45 nm
Thread pitch	4 mm
Max On-seating Pressure	20 mH <sub>2</sub> O
Max Off-seating pressure	20 mH <sub>2</sub> O
L1	345 mm
Thickness valve body	218 mm
Inner Diameter	461.80 mm
Outer Diameter	500 mm
W	595 mm
H1	1030 mm
L	796 mm
Sealed for one-sided pressure	1
Sealed for two-sided pressure	1

- Tests performed at room temperature (16-20°C).  
- Reference point measured from bottom of pipe."

© 2022 Wapro AB. This document is subject to copyrights owned by Wapro AB. Any amendments, republication, retransmission, and/or reproduction of all or any part of the document is expressly prohibited, unless the copyright owner of the material has expressly granted its prior written consent. All other rights are reserved.

**Wapro AB**  
Munkahusvägen 103  
SE-37431 Karlshamn

+46 (0)454 185 10  
wapro@wapro.com

Reg.nr: 556352-1466  
Registered office:  
Karlshamn, Sweden  
VAT nr: SE556352146604

**HOLDING BACK  
THE FLOOD**