



WAGATE® AVSTÄNGNINGSVENTILER

TECHNICAL SPECIFICATION

| | |
|-------------------------------|--|
| Model no. | RVM-TG710 |
| Nominal Diameter | DN/OD 710 |
| Available valve body mtrl. | PE |
| Fasteners mtrl. | AISI 316, Marine grade Stainless Steel |
| Weight | 203 kg |
| Max On-seating Pressure | 10 mH ₂ O |
| Max Off-seating pressure | 10 mH ₂ O |
| Torque nm | 40.00 nm |
| Thread pitch | 5 mm |
| Dimension | 710 mm |
| Øs | 25 mm |
| Torque nm | 40 nm |
| Thread pitch | 5 mm |
| Max On-seating Pressure | 10 mH ₂ O |
| Max Off-seating pressure | 10 mH ₂ O |
| L1 | 508 mm |
| Thickness valve body | 218 mm |
| Inner Diameter | 655.60 mm |
| Outer Diameter | 700 mm |
| W | 812 mm |
| H1 | 1350 mm |
| L | 1122 mm |
| Sealed for one-sided pressure | 1 |
| Sealed for two-sided pressure | 1 |

- Tests performed at room temperature (16-20°C).
- Reference point measured from bottom of pipe."

© 2022 Wapro AB. This document is subject to copyrights owned by Wapro AB. Any amendments, republication, retransmission, and/or reproduction of all or any part of the document is expressly prohibited, unless the copyright owner of the material has expressly granted its prior written consent. All other rights are reserved.

Wapro AB
Munkahusvägen 103
SE-37431 Karlshamn

+46 (0)454 185 10
wapro@wapro.com

Reg.nr: 556352-1466
Registered office:
Karlshamn, Sweden
VAT nr: SE556352146604

**HOLDING BACK
THE FLOOD**