



# WAGATE® AVSTÄNGNINGSVENTILER

## TECHNICAL SPECIFICATION

Model no.	RVM-TG710
Nominal Diameter	DN/OD 710
Available valve body mtrl.	PE
Fasteners mtrl.	AISI 316, Marine grade Stainless Steel
Weight	203 kg
Max On-seating Pressure	10 mH <sub>2</sub> O
Max Off-seating pressure	10 mH <sub>2</sub> O
Torque nm	40.00 nm
Thread pitch	5 mm
Dimension	710 mm
Øs	25 mm
Torque nm	40 nm
Thread pitch	5 mm
Max On-seating Pressure	10 mH <sub>2</sub> O
Max Off-seating pressure	10 mH <sub>2</sub> O
L1	508 mm
Thickness valve body	218 mm
Inner Diameter	655.60 mm
Outer Diameter	700 mm
W	812 mm
H1	1350 mm
L	1122 mm
Sealed for one-sided pressure	1
Sealed for two-sided pressure	1

- Tests performed at room temperature (16-20°C).  
- Reference point measured from bottom of pipe."

© 2022 Wapro AB. This document is subject to copyrights owned by Wapro AB. Any amendments, republication, retransmission, and/or reproduction of all or any part of the document is expressly prohibited, unless the copyright owner of the material has expressly granted its prior written consent. All other rights are reserved.

**Wapro AB**  
Munkahusvägen 103  
SE-37431 Karlshamn

+46 (0)454 185 10  
wapro@wapro.com

Reg.nr: 556352-1466  
Registered office:  
Karlshamn, Sweden  
VAT nr: SE556352146604

**HOLDING BACK  
THE FLOOD**