



WAGATE® AVSTÄNGNINGSVENTILER

TECHNICAL SPECIFICATION

Model no.	SVM-TG560
Nominal Diameter	DN/OD 560
Available valve body mtrl.	PE
Fasteners mtrl.	AISI 316, Marine grade Stainless Steel
Weight	146 kg
Max On-seating Pressure	20 mH ₂ O
Torque nm	56.00 nm
Thread pitch	5 mm
Dimension	560 mm
Øs	25 mm
Torque nm	56 nm
Thread pitch	5 mm
Max On-seating Pressure	20 mH ₂ O
L1	445 mm
Thickness valve body	228 mm
Inner Diameter	517.20 mm
Outer Diameter	560 mm
W	630 mm
H1	1087 mm
L	996 mm
Sealed for one-sided pressure	1

- Tests performed at room temperature (16-20°C).
- Reference point measured from bottom of pipe."

© 2022 Wapro AB. This document is subject to copyrights owned by Wapro AB. Any amendments, republication, retransmission, and/or reproduction of all or any part of the document is expressly prohibited, unless the copyright owner of the material has expressly granted its prior written consent. All other rights are reserved.

Wapro AB
Munkahusvägen 103
SE-37431 Karlshamn

+46 (0)454 185 10
wapro@wapro.com

Reg.nr: 556352-1466
Registered office:
Karlshamn, Sweden
VAT nr: SE556352146604

**HOLDING BACK
THE FLOOD**