



WAGATE® AVSTÄNGNINGSVENTILER

TECHNICAL SPECIFICATION

Model no.	SVM-TG800
Nominal Diameter	DN/OD 800
Available valve body mtrl.	PE
Fasteners mtrl.	AISI 316, Marine grade Stainless Steel
Weight	264 kg
Max On-seating Pressure	10 mH ₂ O
Torque nm	51.00 nm
Thread pitch	5 mm
Dimension	800 mm
Øs	25 mm
Torque nm	51 nm
Thread pitch	5 mm
Max On-seating Pressure	10 mH ₂ O
L1	570 mm
Thickness valve body	208 mm
Inner Diameter	738.80 mm
Outer Diameter	800 mm
W	912 mm
H1	1558 mm
L	1246 mm
Sealed for one-sided pressure	1

- Tests performed at room temperature (16-20°C).
- Reference point measured from bottom of pipe."

© 2022 Wapro AB. This document is subject to copyrights owned by Wapro AB. Any amendments, republication, retransmission, and/or reproduction of all or any part of the document is expressly prohibited, unless the copyright owner of the material has expressly granted its prior written consent. All other rights are reserved.

Wapro AB
Munkahusvägen 103
SE-37431 Karlshamn

+46 (0)454 185 10
wapro@wapro.com

Reg.nr: 556352-1466
Registered office:
Karlshamn, Sweden
VAT nr: SE556352146604

**HOLDING BACK
THE FLOOD**